

DragonFire Racing

3191 N. Washington St. Suite 2

Chandler, AZ 85225

1 (800) 708-9803

WWW.DRAGONFIRERACING.COM



FEEL THE HEAT!

14-1900 - LockDown Ranger XP 900 Harness Bar Installation Instructions

Congratulations on your purchase of the LockDown Ranger XP 900 Harness Bar!

The Ranger XP is one sweet machine but does not allow for use of 4 Point Harnesses. DragonFire has developed a kit for you to get harnesses in your rig safe and securely.



- *Do not use if there are signs of damage
- *Installation may scratch powder coat
- *Use only proper 4-Point Harness with this kit

Disclaimer

Tools Required

T40 Torx Bit

Off road activities can be hazardous and could lead to injury, dismemberment, paralysis and death. No warranty of representation is made as to the products ability to protect the user from any injury or death. The user assumes that risk. The acceptance and /or use of this merchandise purchased from DragonFire by the customer hereby shall release DragonFire from any and all liability pertaining to the use of such merchandise.

Step 1: Place vehicle on flat and level surface and place gear selector in park, remove keys from ignition.

Step 2: Locate and remove top and bottom screws retaining the stock side hip bars from both sides of vehicle. Set hardware aside it will be re-used. (See Figure A)



Dragonfire Racing

Step 3: Place harness bar across backside of seat so that mounting holes align with holes in stock side hip bars and frame of vehicle. Re-Install hardware removed in step 1 and securely fasten. Then re-install bottom hardware from step 1 and securely fasten. (See Figure B)



Step 4: Wrap and install harnesses according to harness manufacture specs. Be sure to run shoulder straps through built in retainers on the harness bar to protect against shoulder strap separation. (See Figure C)



ProTip: Be sure to regularly check hardware and re-tighten if needed.

