



POLARIS RANGER XP 900® 60/40 SEAT COVER

Installation Instructions

1. Remove driver seat bottom. Driver side seat cover will pull around seat allowing elastic to pull seat cover tight under seat. Reinstall seat bottom.
2. Driver backrest pulls over top of seat and attaches using hook and loop straps on sides and bottom. Bottom wraps between seat support bars and attaches with hook and loop strap.
3. Remove passenger seat bottom. Passenger side seat cover will pull around seat allowing plastic clips to hook on openings in seat bottom. Reinstall seat bottom.
4. Passenger backrest pulls over top of seat and attaches using elastic cord with cord lock behind seat backrest.
5. Slip covers around headrests working from outside of unit inward one side of headrest at a time.

Your new seat cover is guaranteed against any defects in material and workmanship for 90 days from the date of purchase. Should any problems arise, please contact your dealer. No warranty card is necessary.

WARNING: Prolonged exposure to direct sunlight may result in fading and/or tendering of the material. Do not store your Ranger with seat cover installed in direct sunlight. Damage resulting from exposure to direct sunlight cannot be warranted.



Greene Mountain Outdoors LLC.
2321 Yellow Banks Road North Wilkesboro, N.C. 28659

www.greenemountain.net

336 670 2186